


250 Alaskan HT



RPM	MPH	GPH	MPG
1000	5.25	1.40	3.75
1500	6.25	2.40	2.60
2000	8.60	3.90	2.21
2500	10.65	5.80	1.84
3000	16.25	8.40	1.93
3500	22.10	10.60	2.08
4000	27.25	12.40	2.20
4500	32.30	15.50	2.08
5000	36.75	18.60	1.98
5500	40.20	25.20	1.60
6000	45.05	31.20	1.44
6100	45.2	31.4	1.44



HEWESCRAFT 250 ALASKAN HT TEST DATE 6/20/18

Length	28'4"
Beam	102"
Dry Weight (Boat Only)	4,600 lbs
Maximum HP	400
Fuel Capacity	190
Weight as tested (Approximate)	5,625 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

YAMAHA F150XB / LF150XB

Horsepower	Twin 150 HP
Displacement	163 CID
Dry Weight (Engine)	489 lbs
Gear Ratio	2:1
Mounting Height	#2

PROPELLERS

Material/Blades	SS/3
Series	Painted SS
Diameter/Pitch	14 1/4 x 17
Yamaha Part #	68F-45972-00-00 / 68G-45972-00-00

TEST CONDITIONS

Number of People	5
Air Temperature (Fahrenheit)	82 ° F
Elevation	1,300 ft.
Wind Velocity	0-5 mph




Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

270 Alaskan HT



RPM	MPH	GPH	MPG
600	3.25	2	1.6
1000	5.35	2	2.7
1500	7.15	4	1.8
2000	9.9	5.5	1.8
2500	13.95	7	2
3000	19.55	9	2.2
3500	25.75	11.5	2.2
4000	31.4	15	2.1
4500	36.9	18.5	2
5000	40.95	23.5	1.7
5500	45.7	31.5	1.5
5800	47.5	33	1.4



HEWESCRAFT 270 ALASKAN HT TEST DATE 4/3/23

Length	30' 4"
Beam	102"
Dry Weight (Boat Only)	5,200lbs
Maximum HP	500
Fuel Capacity	190
Weight as tested (Approximate)	6,020 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

MERCURY TWIN 200

Horsepower	200 Twin HP
Displacement	3.4L
Dry Weight (Engine)	475 lbs
Gear Ratio	1.85:1
Mounting Height	#1

PROPELLERS

Material/Blades	SS/3
Series	Enertia
Diameter/Pitch	14 1/2x17
Mercury Part #	8M0151235/8M151234

TEST CONDITIONS

Number of People	3
Air Temperature (Fahrenheit)	50 ° F
Elevation	1,285 ft.
Wind Velocity	10 mph




Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

270 Alaskan HT



RPM	MPH	GPH	MPG
1500	8.15	3.0	2.7
2000	10.1	4.9	2.1
2500	14.4	6.1	2.4
3000	19.5	7.7	2.5
3500	26.4	11.0	2.4
4000	32.0	13.5	2.4
4500	37.0	18.1	2.0
5000	40.9	21.4	1.9
5500	45.1	30.7	1.5
6000	49.1	36.7	1.3



HEWESCRAFT 270 ALASKAN HT TEST DATE 9/16/22

Length	30' 4"
Beam	102"
Dry Weight (Boat Only)	5,200lbs
Maximum HP	500
Fuel Capacity	190
Weight as tested (Approximate)	6,020 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

MERCURY TWIN 225

Horsepower	225 Twin HP
Displacement	209 CID
Dry Weight (Engine)	475 lbs
Gear Ratio	1.85:1
Mounting Height	#1

PROPELLERS

Material/Blades	SS/3
Series	SS
Diameter/Pitch	14 3/4x17
Mercury Part #	N/A

TEST CONDITIONS

Number of People	4
Air Temperature (Fahrenheit)	65 ° F
Elevation	1,260 ft.
Wind Velocity	0-5 mph




Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

270 Alaskan HT



RPM	MPH	GPH	MPG
1000	3	1.3	2.3
1500	6	2.73	2.2
2000	8	3.48	2.3
2500	12	5.22	2.3
3000	16	6.67	2.4
3500	22	9.17	2.4
4000	27	11.25	2.4
4500	31	14.1	2.2
5000	35	19.44	1.8
5500	38	25.33	1.5
6000	42	32.3	1.3



HEWESCRAFT 270 ALASKAN HT TEST DATE 5/19/18

Length	30' 4"
Beam	102"
Dry Weight (Boat Only)	5,200lbs
Maximum HP	500
Fuel Capacity	190
Weight as tested (Approximate)	6,020 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

YAMAHA F150XB / LF150XB

Horsepower	150 Twin HP
Displacement	163 CID
Dry Weight (Engine)	489 lbs
Gear Ratio	2:1
Mounting Height	#2

PROPELLERS

Material/Blades	SS/3
Series	Painted SS
Diameter/Pitch	14 1/4x17
Yamaha Part #	68F-45972-00-00 / 68G-45972-00-00

TEST CONDITIONS

Number of People	4
Air Temperature (Fahrenheit)	52 ° F
Elevation	1,300 ft.
Wind Velocity	0-5 mph



Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

270 Alaskan HT



HEWESCRAFT 270 ALASKAN HT TEST DATE 6/12/19

Length	30' 4"
Beam	102"
Dry Weight (Boat Only)	5,200lbs
Maximum HP	500
Fuel Capacity	190
Weight as tested (Approximate)	8623 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

YAMAHA F200XCA / 200XCA

Horsepower	200 Twin HP
Displacement	2.8 L
Dry Weight (Engine)	489 lbs
Gear Ratio	1.86:1
Mounting Height	#2

PROPELLERS

Material/Blades	SS/3
Series	Reliance Series
Diameter/Pitch	14 1/4x15
Yamaha Part #	68F-45972-10-00 / 68G-45972-10-00

TEST CONDITIONS

Number of People	4
Air Temperature (Fahrenheit)	60° F
Elevation	1,300 ft.
Wind Velocity	0-5 mph

RPM	MPH	GPH	MPG
1000	6	1.6	3.75
1500	7	2.6	2.69
2000	9	4.0	2.25
2500	11	5.7	1.93
3000	15	7.6	1.97
3500	22	9.5	2.32
4000	28	12.4	2.26
4500	32	14.8	2.16
5000	36	18.4	1.96
5500	41	24	1.71
6100	45	35	1.29



Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

