

290 Adventure HT



290 ADVENTURE HT	TEST DATE 7/12/18
Length	29' 5"
Beam	117"
Dry Weight (Boat Only)	8,500 lbs
Maximum HP	700
Fuel Capacity	250
Weight as tested (Approximate)	9,840 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

HONDA BF 250/BF250

Horsepower	250 Twin HP
Displacement	3.6L
Dry Weight (Engine)	611 lbs
Gear Ratio	2:1
Mounting Height	#2

PROPELLERS

Material/Blades	SS/4
Series	Power Tech Series
Diameter/Pitch	15 1/4x16
Honda Part #	N/A


TEST CONDITIONS

Number of People	5
Air Temperature (Fahrenheit)	85° F
Elevation	1,300 ft.
Wind Velocity	5-10 mph

RPM	MPH	GPH	MPG
1000	5	2.17	2.3
1500	6	2.82	2.13
2000	8	4.62	1.73
2500	9	5.63	1.6
3000	15	8.82	1.7
3500	21	12.35	1.7
4000	26	14.77	1.76
4500	32	20	1.6
5000	37	24.03	1.54
5500	41	32.28	1.27
5900	47	47	1



Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



290 Adventure HT



290 ADVENTURE HT

TEST DATE 7/12/18

Length	29'5"
Beam	117"
Dry Weight (Boat Only)	8500 lbs
Maximum HP	700
Fuel Capacity	250
Weight as tested (Approximate)	10,443 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

YAMAHA BF250UCA/LF250UCA

Horsepower	250 Twins HP
Displacement	4.25L
Dry Weight (Engine)	1,150 lbs
Gear Ratio	1.75:1
Mounting Height	#1

PROPELLERS

Material/Blades	SS/3
Series	Solas
Diameter/Pitch	14 1/4x17
Yamaha Part #	N/A


TEST CONDITIONS

Number of People	5
Air Temperature (Fahrenheit)	75 ° F
Elevation	1,300 ft.
Wind Velocity	5-10 mph

RPM	MPH	GPH	MPG
1000	5	2.3	2.17
1500	7	3.65	1.92
2000	9	5.55	1.62
2500	10	8.7	1.15
3000	12	11.3	1.06
3500	15	14.4	1.04
4000	19.5	18.85	1.03
4500	31	24.75	1.25
5000	37	30.7	1.21
5500	42	39.1	1.07
6000	45.5	46.4	0.98



Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



290 Adventure HT



290 ADVENTURE HT TEST DATE 7/12/18

Length	29'5"
Beam	117"
Dry Weight (Boat Only)	8500 lbs
Maximum HP	700
Fuel Capacity	250
Weight as tested (Approximate)	9,840 lbs

Note: Test weight may include 1/2 tank of fuel, 1 battery, safety & test Equipment

YAMAHA F300UCA/LF300UCA

Horsepower	300 Twin HP
Displacement	4.2L
Dry Weight (Engine)	575 lbs
Gear Ratio	1.75:1
Mounting Height	#1

PROPELLERS

Material/Blades	SS/3
Series	Saltwater Series
Diameter/Pitch	16 1/4x17
Yamaha Part #	N/A

TEST CONDITIONS

Number of People	5
Air Temperature (Fahrenheit)	85 ° F
Elevation	1,300 ft.
Wind Velocity	5-10 mph

RPM	MPH	GPH	MPG
1000	7.5	2.4	3.1
1500	8.5	3.9	2.2
2000	10	6.4	1.6
2500	14	9.1	1.5
3000	16.5	10.6	1.6
3500	27	16.6	1.6
4000	32.5	25.4	1.3
4500	38	29.6	1.3
5000	41	36.3	1.1
5500	44.5	43.2	1.0
5900	47	50.1	.09



Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Hewescraft reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains valuable trademarks belonging to Hewescraft and other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

